

ASTM D 2386- IP 16- NFM 07048- ISO 3013 & DIN 51421

SCOPE:

This test method covers the determination of the temperature below which solid hydrocarbon crystals may form in aviation turbine fuels and aviation gasoline.

APPLICATIONS:

Aviation turbine fuels and aviation gasoline.

**FREEZING POINT OF AVIATION FUELS
- REF 513461 -**

Complete freezing point apparatus, comprising:

- ✓ Jacketed sample tube
- ✓ Brass packing gland for stirrer
- ✓ Brass wire stirrer
- ✓ Vacuum flask unsilvered
- ✓ With support and thermometer
- ✓ Dimensions : 200 x 200 x 450 mm –
- ✓ Weight: ± 5 kg.

NECESSARY ACCESSORY

REF 941597 Dry ice machine

REFERENCE FLUID

REF 60025 Congealing point (kerosene) @ - 48.9°C

SPARE PARTS

REF 513462 Jacketed sample tube, double walled

REF 9415562 Gland, brass packing for stirrer

REF 9415563 Stirrer

REF 9415564 Vacuum flask unsilvered

REF 11566 ASTM thermometer (114 C), range from -80 to +20°C

RE 513463 Cork for sample tube



AUTOMATIC EQUIPMENT ON REQUEST

NORMALAB FRANCE SAS

14 rue des Lilas - F-76 210 Lintot

Tel. : +332 35 38 59 59 - Fax : +332 35 38 78 55

NORMALAB BELGIUM S.A.

Parc Industriel

28 rue des Pieds-d'Alouette - BE-5100 NANINNE / Belgium

Tel : +32 81 71 19 90 - Fax : +32 81 22 27 01

DISTRIBUTED BY